



INTERNATIONAL WATER TREATMENT SPECIALISTS

## Tanburn No. 2 Fuel Oil Additive

**TANBURN - 2** is a dark brown slightly viscous liquid containing emulsifiers, surfactants, combustion improvers and corrosion inhibitors. TANBURN - 2 contains special heavy duty additives to cope with serious combustion problems. TANBURN - 2 is designed for treating heavy and light fuel oils in boilers and stationary diesel engines.

**TANBURN - 2** is a before and after burner treatment which :-

- Gives better fluidity in holding tanks by helping to suspend and disperse the heavier hydrocarbons and sludge forming waxes and tars.
- Prevents water build up in tanks by emulsifying small traces as they form and carrying them through to the burner.
- Provides a continual cleaning and corrosion preventing action in tanks and lines which minimises blockages normally caused by corrosion products.
- Helps to improve atomisation at the burner which minimises smoking and gives better fuel economy.
- Is very economical in use providing real practical benefits at very low dose levels.

### DOSAGES

TANBURN - 2 should be dosed at the rate of 1 litre per 10,000 - 12,000 litres of fuel oil. For best mixing, the TANBURN - 2 should be added to the storage tank before filling.

### HANDLING

TANBURN - 2 should not come into contact with skin or eyes and gloves and goggles should be used when handling. If splashing occurs, wash immediately with copious quantities of water. Keep the product out of the reach of children. Refer product M.S.D.S. for further details.

**PLEASE NOTE:** TANBURN - 2 and its raw materials are combustible liquids that will burn if involved in a fire.

### PACKAGING

TANBURN - 2 is packed in 20 litre and 205 litre steel drums.

