



INTERNATIONAL WATER TREATMENT SPECIALISTS

Tandex Antifoam SD Foam Emulsion

ANTIFOAM SD is a milky white general purpose foam control additive.

ANTIFOAM SD is designed specifically for the control of foaming problems in aqueous systems.

FEATURES

- Quick action - immediate de-foaming
- Stable - good storage properties
- Economical - effective at low doses
- Non toxic - safe to use
- Low viscosity - easy to handle

APPLICATIONS

ANTIFOAM SD is suitable for almost all foam control applications associated with water based systems. This would include chemical cleaning processes, metal treatment procedures, boiler water treatment, cooling tower treatment and waste water processing.

HOW TO USE

Dosage of ANTIFOAM SD will be governed by many variables such as type of operations, agitation, temperature and time limitations. However a reasonable starting point would be to dose 1 litre of ANTIFOAM SD for every 1000 litres of solution to be treated. Dosages can be increased or decreased depending upon results achieved.

HANDLING

ANTIFOAM SD is a very low toxicity type product, and no special handling procedures are necessary. However, as with all chemicals, good basic housekeeping is recommended and safety glasses and PVC gloves are recommended where splashing or continuous contact with the product is likely.

PACKAGING

ANTIFOAM SD is packed in 250ml, 1 litre, and 15 litre drums.

