

ROVSKI Bitumen Undercoat

Rovski Bitumen Undercoat is an anticorrosion protective product formulated with waxes and sulfonates, solvent based. It is used for underbody protection of various vehicles against corrosion development. It also can protect the substrate which has not been coated with electrocoating paint.

a). Characteristics

1. Wide range of application.
2. Easy application.
3. Excellent performance.

b). Properties

Appearance	: Black paste
Viscosity	: 30 000 cps – 80 000 cps @ 28 ± 2 °C
Specific Gravity	: 0.95 – 1.05
Non Volatile Content	: 68% - 74%

c). Applications

As with all surface coatings, preparation of the surface is of great importance and will influence the degree of adhesion obtained. ROVSKI Bitumen Undercoat can be applying by brush or airless spray.

d). Precaution

1. Flammable. Keep away from source of ignition.
2. Use in well ventilated area.
3. Use protective clothing to avoid direct skin contact.
4. Store in cool and dry area.
5. Store with tightly sealed and undamaged containers.

e). Packaging

Metal container 20 L

The information given above is true and is based on our own study and research work and experience. ROVSKI Industries Sdn Bhd does not provide warranty or guarantee for products made at different conditions for which are beyond our control. All separate trial cases should be studied and tested to obtain own parameter before any order and delivery.