

Tape Type Butyl Compound **ROVSKI 906 Grey**

Rovski 906 Grey is a butyl rubber sealing tape for non-critical sealing and glazing application in drainage system. Provides economical installation because of its form and ease of handling.

a). Characteristics

1. It has some degree of pressure sensitivity and is sufficiently soft for ease of compression during installation.
2. It has good weather and ageing resistance.
3. It is relatively flexible and does not harden.
4. It does not stain.

b). Properties

Needle Penetration	: 30 - 50
Specific Gravity	: 1.75 – 1.85
Appearance	: Light grey compound
Shear Strength	: 0.90 – 1.50 kgf/cm ²
Peel Adhesion	: 0.10 – 0.50 kgf/cm ²
Tensile Strength	: 0.90 – 1.50 kgf/cm ²
Water Absorption	: < 1.00%

c). Applications

1. Ready to use as tape sealer, reeled up with release paper.
2. It is pre-cut at a fixed length.
3. Peel off the tape from the release paper and simply apply.
4. Area of application must dry, clean, free from dirt and oil.
5. Application temperature ranges from 5°C to 40 °C.

d). Precaution

1. Store in a cool, dry and clean place.
2. Avoid unnecessary exposure to dust.
3. To avoid deformation, store vertically and do not put heavy objects onto tapes.

e). Packaging

16 mm x 3.8 m

10 rolls in a box

(Other sizes and packing available upon request and subjected to arrangement).